



Catalog Number	ANSI Class	Ultimate Strength (lbs.)	Bolt Size	Approx. Ship Wt. (lbs.)	Std. Pkg. Qty.
P531G	53-1	2,000	5/8	0.46	100
P532G	53-2	3,000	5/8	1.20	50
P533G	53-3	4,000	5/8	1.38	50
P534G	53-4	4,500	5/8	2.56	24
P535G	53-5	6,000	5/8	2.72	24

ANSI - 70 Gray Glaze is Standard



**POWERLINE HARDWARE**

245, North Lane Avenue, Jacksonville,  
Florida 32254

Phone : 904-695-9880

Fax : 904-695-9717

Website : [www.powerlinehardware.com](http://www.powerlinehardware.com)

## Specification Number - C29.3

Catalog Number	P531G	P532G	P533G	P534G	P535G
ANSI Class	53-1	53-2	53-3	53-4	53-5

### Mechanical Values

Transverse Strength (lbs.)	2,000	3,000	4,000	4,500	6,000
----------------------------	-------	-------	-------	-------	-------

### Electrical Values

Low Frequency Dry Flashover (kV)	20	25	25	25	35
Low Frequency Wet Flashover, Vertical (kV)	8	12	12	12	18
Low Frequency Wet Flashover, Horizontal (kV)	10	15	15	15	25

### Packing & Shipping Data

Net Weight Each (lbs.)	0.44	1.14	1.21	2.42	2.65
Packed Weight Each (lbs.)	0.46	1.20	1.38	2.56	2.72
Standard Package Qty.	60	50	50	25	25

ANSI - 70 Gray Glaze is standard.

For Brown or White Glaze add "B" or "W" to catalog number suffix.



**POWERLINE HARDWARE**

245, North Lane Avenue, Jacksonville,  
Florida 32254

Phone : 904-695-9880

Fax : 904-695-9717

Website : [www.powerlinehardware.com](http://www.powerlinehardware.com)